

FEATURES

Methods to initiate regeneration:

Meter Immediate

Meter Delayed

Time Clock Delay

Auxiliary Input

Modbus Initiated

Network up to 16 valves using Cat5 cable

Add up to 2 relay expansion boards to circuit board

Top or side mount capabilities

Blue backlight front display

Reliable and proven DC drive

Battery backup with 8 hour carry over

Modus RS485 duplex to communicate with building automation systems

Programmable System types:

Alternating

Progressive Flow

Series

Single

On-Site circuit board software update capability

BENEFITS



Improved employee & customer



Improved Water Quality



Consistent product quality



Minimize scale build up



Energy Efficiency



Extend Equipment lifespan



Reduce maintenance Costs

OVERVIEW

The Aqua Magic Pro 3" Series is ideal for large commercial or industrial uses and provides up to 250 GPM service flow rate. This system is equipped with pre or post-treated water regenerant refill, a reliable DC Drive, and backwash and brining capabilities for tanks up to 63" in diameter. Assembled using NSF-certified components.



MADE IN THE

SOLD BY

6 FRAKCO

YOUR COMPLETE WATER CONDITIONING HEADQUARTERS

500 N Blue Mound Ave, Luverne, MN 56156 507-283-4416 | www.frakco.com